

## **Certificate of Analysis**

Product Number:	S020101	CAS Number:	7697-37-2
Product Description:	Nitric Acid	Molecular Weight:	63.01 g/mol
Product Grade:	BASELINE®	Molecular Formula:	HNO <sub>3</sub>
Lot Number:	1224110	Density:	1.41 g/mL
Release Date:	11/22/2024 (mm/dd/yyyy)	Molarity:	16 moles/litre
Expiration Date:	11/22/2027 (mm/dd/yyyy)	Normality:	16 moles/litre

Analytical Data							
Analyte	Specification	Actual Value	Analyte	Specification	Actual Value		
Assay (HNO <sub>3</sub> )	67 - 70% w/w	68% w/w	Molybdenum (Mo)	10 ppt	< 0.1 ppt		
Aluminum (Al)	20 ppt	< 5 ppt	Neodymium (Nd)	1 ppt	< 0.01 ppt		
Antimony (Sb)	10 ppt	< 0.1 ppt	Nickel (Ni)	20 ppt	< 1 ppt		
Arsenic (As)	20 ppt	< 0.05 ppt	Niobium (Nb)	1 ppt	< 0.05 ppt		
Barium (Ba)	10 ppt	< 0.05 ppt	Palladium (Pd)	20 ppt	< 0.1 ppt		
Beryllium (Be)	10 ppt	< 0.05 ppt	Platinum (Pt)	20 ppt	< 0.1 ppt		
Bismuth (Bi)	10 ppt	< 0.01 ppt	Potassium (K)	10 ppt	< 5 ppt		
Boron (B)	10 ppt	< 2 ppt	Praseodymium (Pr)	1 ppt	< 0.01 ppt		
Cadmium (Cd)	10 ppt	< 0.01 ppt	Rhenium (Re)	10 ppt	< 0.01 ppt		
Calcium (Ca)	10 ppt	< 10 ppt	Rhodium (Rh)	10 ppt	< 0.01 ppt		
Cerium (Ce)	10 ppt	< 0.01 ppt	Rubidium (Rb)	10 ppt	< 0.01 ppt		
Cesium (Cs)	10 ppt	< 0.01 ppt	Ruthenium (Ru)	20 ppt	< 0.01 ppt		
Chromium (Cr)	10 ppt	< 0.5 ppt	Samarium (Sm)	1 ppt	< 0.01 ppt		
Cobalt (Co)	10 ppt	< 0.2 ppt	Scandium (Sc)	10 ppt	< 0.01 ppt		
Copper (Cu)	10 ppt	<0.5 ppt	Selenium (Se)	Information Only	< 5 ppt		
Dysprosium (Dy)	1 ppt	< 0.01 ppt	Silver (Ag)	10 ppt	< 0.01 ppt		
Erbium (Er)	1 ppt	< 0.01 ppt	Sodium (Na)	10 ppt	< 5 ppt		
Europium (Eu)	1 ppt	< 0.01 ppt	Strontium (Sr)	10 ppt	< 0.02 ppt		
Gadolinium (Gd)	1 ppt	< 0.01 ppt	Tantalum (Ta)	Information Only	< 10 ppt		
Gallium (Ga)	10 ppt	< 0.05 ppt	Tellurium (Te)	1 ppt	< 0.01 ppt		
Germanium (Ge)	10 ppt	< 0.05 ppt	Terbium (Tb)	1 ppt	< 0.01 ppt		
Gold (Au)	20 ppt	< 1 ppt	Thallium (TI)	10 ppt	< 0.01 ppt		
Hafnium (Hf)	10 ppt	< 0.01 ppt	Thorium (Th)	1 ppt	< 0.01 ppt		
Holmium (Ho)	1 ppt	< 0.01 ppt	Thulium (Tm)	1 ppt	< 0.01 ppt		
Indium (In)	1 ppt	< 0.01 ppt	Tin (Sn)	20 ppt	< 0.05 ppt		
Iron (Fe)	10 ppt	< 2 ppt	Titanium (Ti)	10 ppt	< 0.2 ppt		
Lanthanum (La)	1 ppt	< 0.01 ppt	Tungsten (Ŵ)	10 ppt	< 0.1 ppt		
Lead (Pb)	10 ppt	< 0.01 ppt	Uranium (U)	1 ppt	< 0.01 ppt		
Lithium (Li)	10 ppt	< 0.01 ppt	Vanadium (V)	10 ppt	< 0.02 ppt		
Lutetium (Lu)	1 ppt	< 0.01 ppt	Ytterbium (Yb)	1 ppt	< 0.01 ppt		
Magnesium (Mg)	10 ppt	< 0.5 ppt	Yttrium (Y)	1 ppt	< 0.01 ppt		
Manganese (Mn)	10 ppt	< 0.05 ppt	Zinc (Zn)	10 ppt	< 1 ppt		
Mercury (Hg)	50 ppt	< 5 ppt	Zirconium (Zr)	10 ppt	< 0.5 ppt		

Greg Henson QA & RA Manager Most elements are determined by high resolution ICP-MS using sample preconcentration. The results are an average of three aliquots subsampled from three samples representative of the lot. The samples are slowly evaporated to dryness. The resulting residue is reconstituted in a small volume of SEASTAR™ **BASELINE**® 2% Nitric Acid / 2% Hydrogen Peroxide. For volatile elements (indicated by \*), the acid samples are diluted then directly injected into the ICP-MS. Values below three times the standard deviation of the blank are shown with '<', no blank value is subtracted.

For terms and conditions of use, please see page 2.

SEASTAR CHEMICALS ULC 2061 Henry Avenue West, Sidney, BC, Canada V8L 5Z6 Phone: 1-250-655-5880 | Toll free: 1-800-663-2330 (North America only) www.seastarchemicals.com



# **Terms and Conditions of Use**

### Safety Guidelines:

PRIOR to opening or storing this product be sure to consult the Safety Data Sheet (SDS) to ensure safe storage and handling with regards to this hazardous material. This information must be read and understood prior to use or storage.

SAFETY HANDLING NOTES: Consult the SDS PRIOR to handling this product. Use proper safety apparel according to the recommendations of the SDS. Exposure controls and personal protection should include: a properly functioning fume hood, protection for eyes (safety glasses), hands (chemically compatible gloves), feet (chemically compatible boots), and exposed skin (splash protection and a chemically compatible apron). All of these items must conform to local/regional/national regulatory requirements.

#### SEASTAR<sup>™</sup>'s Product Integrity Guidelines:

We have found our products, unopened and sealed, maintain the certified integrity, or product quality, for their stated certification period under the following conditions:

- Store at room temperature, maximum range 15°C (59°F) to 25°C (77°F).
- Avoid exposure to sunlight or ultraviolet light sources.
- Open in a 'particle free' environment. SEASTAR recommends a HEPA or ULPA particle filtered trace metal clean room. Open product should be handled under Class 100 or ISO 5 clean room or better conditions.

Once opened, product integrity will depend on proper handling and exposure to contaminants. To reduce trace metal contamination, the inner pack of plastic bags and bottle should be opened under Class 100 or ISO 5 clean room or better conditions to maintain the integrity of the product. The use of plastic gloves, hair net and a clean room suit is also advised.

#### For SEASTAR™'s Product Expiration Policy and Product Permeation FAQ, please see our website.

#### Notes:

Reported density, molarity and normality values reflect published literature and are characteristic of the product's assay range. If you require an accurate density, molarity, or normality for the product that you have purchased, you will have to perform the measurement. Bottles within a given lot have small assay variations.

### **Definitions**:

- Actual value: the measured value in a particular lot analysis.
- Analyte: the substance being measured.
- Specification: the maximum certified value of an analyte, unless otherwise specified.
  - **Unit(s): ppm** part per million or μg (microgram) of analyte per gram of solution. **ppb** – part per billion or ng (nanogram) of analyte per gram of solution. **ppt** – part per trillion or pg (picogram) of analyte per gram of solution.

Greg Henson QA & RA Manager