CERTIFICATE OF ANALYSIS

BASELINE[®] Nitric Acid

1A																			
1.1		PRODUCT NUMBER: 01				LOT NU	MBER:	1204	4020		ASSAY: 69%								
	2A											3A	4A	5A	6A	7A			
3 Li <1	4 Be <5	average of three aliquots subsampled from three samples representative of the lot. The samples are slow ly evaporated to dryness, the resulting residue is reconstituted in a small volume of 2% SEASTAR [™] BASELINE [®]																	
11 Na <10	12 Mg <5										times the	<mark>13 Al</mark> <10							
_	_	3B	4B	5B	6B	7B	_	8		1B	2B								
19 К <10	20 C a <20	21 Sc <1	22 Ti <10	23 V <1	24 Cr <10	25 Mn <2	26 Fe <20	27 Co <1	28 Ni <10	29 Cu <3	30 Zn <20	31 Ga <1	32 Ge <1	33 As <10	34 Se <20				
37 Rb <1	38 Sr <1	39 Y <1	40 Zr <1	41 Nb <1	42 Mo <1	1	44 Ru <10	45 Rh <1	46 Pd <10	47 Ag <2	48 Cd <1	49 In <1	50 Sn <20	51 Sb <10	52 Te <5				
55 Cs <0.05	56 Ba <1	57 La <0.05	72 Hf <0.05	73 Ta <10	74 W <5	75 Re <1			78 Pt <1	79 Au <10	80 *Hg <100	81 TI <0.1	82 Pb <1	83 Bi <0.1					
											-						1		

ALL VALUES ARE REPORTED IN PARTS PER TRILLION (PPT)

KEY																		1.				
(1) (2)	(1) Atomic Number	58 Ce	59 Pr	60 Nd		62 Sm	63	Eu	64	Gd	65 Tb	66	Dy	67	Но	68 Er	r 69	Tm	70	Yb	71	Lu
(3)	(3) (2) Elemental Symbol		< 0.05	<0.05		<0.01	<0	0.01	<0.0	01	<0.01	<0	0.01	<0	.01	<0.01	<(0.01	<0	.01	<0	.01
(4)	4) (3) Concentration (mean							1.1														
	in ppt)	90 Th		92 U																		
	(4) 1 Standard	<0.05		<0.01																		
	Deviation n=3)				1.00	1.1								1.1								
										Release Date:												
					B M: Kelvey								Ex	piry	/ Date:	Ма	rch	2, 2(007			
	BASELINE					Dr. B. M QA/QC M							174				10.215.1	-				
											SEASTAR CHEMICALS INC											



Product Integrity:

Based on extensive testing results, SEASTAR CHEMICALS INC have found our products, unopened and sealed, maintain the certified integrity, or product quality, for a minimum of three years under the following conditions:

- Stored at room temperature, maximum range 15°C (59°F) to 25°C (77°F).
- Minimum exposure to light.
- For limited time, storage/transport temperature range 5°C (41°F) to 35°C (95°F)

Upon opening the product, the product's integrity will depend on proper handling and exposure to contaminants. The product has been bottled under CLASS 100 clean room conditions, to maintain the certified quality it should be used under these conditions.

Prior to opening or storing this product be sure to consult the Material Safety Data Sheet (MSDS) Section 7 Handling and Storage to ensure safe storage and handling with regards to this hazardous material. This information must be understood prior to its use or storage.

A further note to reduce trace metal contamination: The inner pack of plastic bags and bottle should be opened under CLASS 100 particle conditions to maintain the integrity of the product. The use of plastic gloves, hair net and a clean room suit is also advised.

Appropriate safety precautions must be taken as well as wearing the required safety apparel. A properly functioning fumehood, protection for eyes, hands, feet and exposed skin must also be worn. All of these items must conform to local/regional/national regulatory requirements.

Dr. B. McKelvey QA/QC Manager

10005 McDonald Park Road, Sidney, BC, Canada V8L 3S8 phone: (250) 655-5880 fax: (250) 655-5888 toll free: 1 (800) 663-2330 (within Canada & U.S. only) Email: seastar.chemicals@axys.com web: www.seastarchemicals.com