CERTIFICATE OF ANALYSIS

BASELINE® Nitric Acid

1A	PRODUCT NUMBER: S020101						LOT NUMBER: 1210100 AS				ASS	SSAY (HNO ₃ , w/w): 69%					
3 Li < 0.5	2A 4 Be < 1	average evaporate Nitric Acid	of three aliced to drynes	quots subsass. The resu ogen Peroxi	ampled from ulting residu ide. Operati	n three sam e is reconst ons are con	ples repres tuted in a s ducted und	sentative of mall volume er Class 10	concentration the lot. The of SEASTA or better cl	e samples a AR [™] BASEL ean-room c	are slowly INE® 2% conditions.	3A 5 B < 10	4A	5A	6A	7A	
11 Na < 5	< 5	below 3 ti 3B	mes the sta 4B	ndard devia	tion of the b	ank are sho	wn with '<',	no blank va	vinjected int lue is subtra	cted. 1B	2B	13 AI < 10					
19 K < 5	< 10	< 1	< 5	< 0.5	24 Cr < 10	< 1	< 10	< 1	28 Ni < 5	< 5	30 Zn < 1	< 0.1	< 0.1	< 10	34 Se < 5		
37 Rb	38 Sr < 1	39 Y < 0.1	40 Zr < 0.5	< 1	< 1		44 Ru < 1	45 Rh	46 Pd < 5	47 Ag < 0.5	< 0.1	< 0.1	50 Sn < 5	51 Sb < 5	52 Te < 0.5		*,
55 Cs < 0.05	56 Ba < 1	57 La < 0.05	72 Hf < 0.05	73 Ta < 10	74 W < 1	75 Re < 0.1			78 Pt < 1	79 Au < 1	80 Hg < 5	81 TI < 0.05	82 Pb < 0.5	83 Bi < 0.05			

ALL VALUES ARE REPORTED IN PARTS PER TRILLION (PPT)

	NE Y	.(1)	Atomic Number
l	(1) (2)	(2)	Elemental Syml
	(3)	(3)	Concentration (
	(4)		in ppt)
ı		(4)	1 Standard Dev
			(N=3)

	58
bol	
mean	
viation	90

	58 Ce	59 Pr	60 Nd	62 Sm	63 Eu	64 Gd	65 Tb	66 Dy	67 Ho	68 Er	69 Tm	70 Yb	71 Lu
	< 0.05	< 0.05	< 0.05	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01
וו	199												
	90 Th		92 U										
'	< 0.05		< 0.01										
	- 4												

HNO₃ (67 - 70%): Properties

Molar Mass: 63.01g/mol

Density: 1.41 g/ml

Molarity: 16 moles/litre

Normality: 16 moles/litre

Release Date: November 4, 2010 Expiry Date: November 4, 2013



Dr. B. McKelvey QA/QC Manager



Product Integrity:

Based on extensive testing results, SEASTAR CHEMICALS INC have found our products, unopened and sealed, maintain the certified integrity, or product quality, for a minimum of three years under the following conditions:

- Stored at room temperature, maximum range 15°C (59°F) to 25°C (77°F).
- Minimum exposure to light.
- For limited time, storage/transport temperature range 5°C (41°F) to 35°C (95°F)

Upon opening the product, the product's integrity will depend on proper handling and exposure to contaminants. The product has been bottled under CLASS 100 clean room conditions, to maintain the certified quality it should be used under these conditions. Furthermore to reduce trace metal contamination, the inner pack of plastic bags and bottle should be opened under CLASS 100 particle conditions to maintain the integrity of the product. The use of plastic gloves, hair net and a clean room suit is also advised.

Safety:

PRIOR to opening or storing this product be sure to consult the Material Safety Data Sheet (MSDS) Section 7 Handling and Storage to ensure safe storage and handling with regards to this hazardous material. This information must be understood prior to its use or storage.

SAFETY HANDLING NOTES: Consult your MSDS, PRIOR to handling these materials. Use proper safety apparel according to the recommendations of the MSDS. Exposure controls and personal protection should include: a properly functioning fume hood, protection for eyes (safety glasses), hands (chemically compatible gloves), feet (chemically compatible boots) and exposed skin (splash protection and a chemically compatible apron). All of these items must conform to local/regional/national regulatory requirements.

Dr. B. McKelvey QA/QC Manager

B MªZ

10005 McDonald Park Road, Sidney, BC, Canada V8L 5Y2

phone: (250) 655-5880 fax: (250) 655-5888

toll free: 1 (800) 663-2330 (within Canada & U.S. only) Email: seastar.technicals.upport@seastarchemicals.com

Web: www.seastarchemicals.com