CERTIFICATE OF ANALYSIS

BASELINE[®] Sulfuric Acid

		PRODU	JCT NU	MBER:	03		LOT NU	MBER:	3202	2112			ASSAY:	96%			
3 Li <5	2A 4 Be <5	Be Most elements are determined by magnetic sector ICP-MS using sample preconcentration. The results are an average of three aliguots subsampled from three samples representative of the lot. The samples are slow ly											4A	5A	6A	7A	
11 Na <50	12 Mg <10	volatile elements (indicated by *), the acid samples are diluted then directly injected into the ICP-MS. Values below 3 times the standard deviation of the blank are show n with "<", no blank value is subtracted. 3B 4B 5B 6B 7B 8 1B 2B										13 AI <20					
19 К <50	20 C a <50	21 Sc <5	22 Ті <50	23 V <5	24 Cr <10	25 Mn <1	26 Fe <20	27 Co <1	28 Ni <20	29 Cu <5	30 Zn <20	<mark>31 Ga</mark> <1	32 Ge <100	33 *As <500	34 *Se <500		
37 Rb <1	38 Sr <1	39 Y <1	40 Zr <5	41 Nb <1	42 Mo <10			<mark>45 Rh</mark> <1	46 Pd <10	47 Ag <2	48 Cd <1	<mark>49 In</mark> <1	50 Sn <50	51 Sb <10	52 Те <10		
55 Cs <1	56 Ba <10	57 La <1	72 Hf <0.1	73 Ta <10	74 W <5				78 Pt <1		80 *Hg <100	81 TI <1	82 Pb <5	83 Bi <1			

ALL VALUES ARE REPORTED IN PARTS PER TRILLION (PPT)

KEY									1.1						
(1) (2)	(1) Atomic Number	58 Ce	59 Pr	60 Nd	1.1	62 Sm	63 Eu	64 Gd	65 Tb	66 Dy	67 Ho	68 Er	69 Tm	70 Yb	71 Lu
(3)	(2) Elemental Symbol	<0.1	<0.1	<0.1	1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1
(4)	(3) Concentration (mean		i												
	in ppt)	90 Th		92 U											
	(4) 1 Standard	<0.1	S	<0.1											
	Deviation n=3)		12.75					1							
	B									Release Date: October 8, 2003 Expiry Date: October 8, 2006					
		B Mc Kelver													
	BASELINE				Dr.	B. McKelve QC Manag	y			Ø∭0 SE	ASTAR	CHE	MICA	LS INC	5



Product Integrity:

Based on extensive testing results, SEASTAR CHEMICALS INC have found our products, unopened and sealed, maintain the certified integrity, or product quality, for a minimum of two years under the following conditions:

- Stored at room temperature, maximum range 15°C (59°F) to 25°C (77°F).
- Minimum exposure to light.
- For limited time, storage/transport temperature range 5°C (41°F) to 35°C (95°F)

Upon opening the product, the product's integrity will depend on proper handling and exposure to contaminants. The product has been bottled under CLASS 100 clean room conditions, to maintain the certified quality it should be used under these conditions.

Prior to opening or storing this product be sure to consult the Material Safety Data Sheet (MSDS) Section 7 Handling and Storage to ensure safe storage and handling with regards to this hazardous material. This information must be understood prior to its use or storage.

A further note to reduce trace metal contamination: The inner pack of plastic bags and bottle should be opened under CLASS 100 particle conditions to maintain the integrity of the product. The use of plastic gloves, hair net and a clean room suit is also advised.

Appropriate safety precautions must be taken as well as wearing the required safety apparel. A properly functioning fumehood, protection for eyes, hands, feet and exposed skin must also be worn. All of these items must conform to local/regional/national regulatory requirements.

Dr. B. McKelvey QA/QC Manager

10005 McDonald Park Road, Sidney, BC, Canada V8L 3S8 phone: (250) 655-5880 fax: (250) 655-5888 toll free: 1 (800) 663-2330 (within Canada & U.S. only) Email: seastar.chemicals@axys.com web: www.seastarchemicals.com