## CERTIFICATE OF ANALYSIS

## **BASELINE®** Sulfuric Acid

1A PRODUCT NUMBER: BA-03

**LOT NUMBER: 3205073** 

ASSAY (H<sub>2</sub>SO<sub>4</sub>, w/w): 95%

												` -	-T-	•			
3 Li	2A 4 Be		ments are d									3A	4A	5A	6A	7A	
<10	<5	COV OF A OT A DIM DA C CLINIC															
11 Na <30	<b>12 Mg</b> <10	elements (indicated by *), the acid samples are diluted then directly injected into the ICP-MS. Values below 3															
		3B	4B	5B	6B	7B		8		1B	2B						
19 K	20 Ca	21 Sc	22 Ti	23 V	24 Cr	25 Mn	26 Fe	27 Co	28 Ni	29 Cu	30 Zn	31 Ga	32 Ge	33 As*	34 Se*		
<50	<50	<5	<50	<5	<10	<1	<30	<1	<20	<5	<20	<1	<100	<500	<500		
37 Rb	38 Sr	39 Y	40 Zr	41 Nb	42 Mo	1111		45 Rh	46 Pd	47 Ag	48 Cd	49 In	50 Sn	51 Sb	52 Te		
<1	<1	<1	<5	<1	<10			<1	<10	<5	<1	<1	<50	<10	<10		
55 Cs	56 Ba	57 La	72 Hf	73 Ta	74 W				78 Pt		80 Hg*	81 TI	82 Pb	83 Bi			
<1	<10	<1	<0.1	<20	<5				<10		<100	<1	<5	<1			
		4		1													

## ALL VALUES ARE REPORTED IN PARTS PER TRILLION (PPT)

(1) (2) (3) (4)

(1) Atomic Number (2) Elemental Symbol

(3) Concentration (mean in ppt)

(4) 1 Standard Deviation (N=3)

	58	Се	59 Pr	60 Nd	62 Sm	63 Eu	64 Gd	65 Tb	66 Dy	67 Ho	68 Er	69 Tm	70 Yb	71 Lu
	<0.	1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1
n l														
	90	Th		92 U										
n	<0.	1		<0.1										


Release Date:

December 7, 2005

**Expiry Date:** 

December 7, 2008







## **Product Integrity:**

Based on extensive testing results, SEASTAR CHEMICALS INC have found our products, unopened and sealed, maintain the certified integrity, or product quality, for a minimum of three years under the following conditions:

- Stored at room temperature, maximum range 15°C (59°F) to 25°C (77°F).
- Minimum exposure to light.
- For limited time, storage/transport temperature range 5°C (41°F) to 35°C (95°F)

Upon opening the product, the product's integrity will depend on proper handling and exposure to contaminants. The product has been bottled under CLASS 100 clean room conditions, to maintain the certified quality it should be used under these conditions.

Prior to opening or storing this product be sure to consult the Material Safety Data Sheet (MSDS) Section 7 Handling and Storage to ensure safe storage and handling with regards to this hazardous material. This information must be understood prior to its use or storage.

A further note to reduce trace metal contamination: The inner pack of plastic bags and bottle should be opened under CLASS 100 particle conditions to maintain the integrity of the product. The use of plastic gloves, hair net and a clean room suit is also advised.

Appropriate safety precautions must be taken as well as wearing the required safety apparel. A properly functioning fumehood, protection for eyes, hands, feet and exposed skin must also be worn. All of these items must conform to local/regional/national regulatory requirements.

Dr. B. McKelvey QA/QC Manager

10005 McDonald Park Road, Sidney, BC, Canada V8L 3S8

phone: (250) 655-5880 fax: (250) 655-5888

toll free: 1 (800) 663-2330 (within Canada & U.S. only)

Email: seastar.chemicals@axys.com web: www.seastarchemicals.com