## CERTIFICATE OF ANALYSIS

# **BASELINE®** Sulfuric Acid

1A PRODUCT NUMBER: S020301

LOT NUMBER: 3213121

ASSAY (H<sub>2</sub>SO<sub>4</sub>, w/w): 95%

	2A								concentration			3A	4A	5A	6A	7A	
3 Li < 1	<b>4 Be</b> < 0.01								the lot. The of SEASTA								
	0.01	Nitric Aci	d / 2% Hydro	ogen Peroxi	ide. Operation	ons are con	ducted und	er Class 100	or better cl	ean-room c	onditions.						
11 Na	_								injected into lue is subtrac		S. Values	13 AI					
< 50	< 0.5	3B	4B	5B	6B	7B	,	8		1B	2B	< 10					
19 K	20 Ca	21 Sc			24 Cr		26 Fe	27 Co	28 Ni		30 Zn	31 Ga	32 Ge	33 As*	34 Se*		
< 20	< 25	< 0.1	< 1	< 0.05	< 0.5	< 0.05	< 5	< 0.05	< 1	< 5	< 5	< 0.05	< 20	< 500	< 500		
37 Rb	38 Sr	39 Y	40 Zr	41 Nb	42 Mo	5.0	-	45 Rh	46 Pd	47 Ag	48 Cd	49 In	50 Sn	51 Sb	52 Te		
< 0.01	< 0.1	< 0.05	< 0.5	< 0.05	< 0.5	1		< 0.01	< 10	< 0.05	< 0.01	< 0.01	< 0.5	< 0.05	< 0.01		
55 Cs	56 Ba	57 La	72 Hf	73 Ta	74 W		-		78 Pt	-	80 Hg*	81 TI	82 Pb	83 Bi			
< 0.01	< 0.1	< 0.05	< 0.01	< 20	< 0.5				< 10		< 50	< 0.01	< 0.5	< 0.01			

#### ALL VALUES ARE REPORTED IN PARTS PER TRILLION (PPT)

KEY (1) Ato (1) (2) (2) Elo (3) (3) Co

(4)

(1) Atomic Number

(2) Elemental Symbol (3) Concentration (mean

in ppt)
(4) 1 Standard Deviation
(N=3)

ſ	58 (	Се	59 Pr	60 Nd	111	62 Sm	63 Eu	64 Gd	65 Tb	66 Dy	67 Ho	68 Er	69 Tm	70 Yb	71 Lu
	< 0.5	5	< 0.01	< 0.1		< 0.01	< 0.01	< 0.05	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01
n															
Ξ	90	Th		92 U											
ı	< 0.0	1		< 0.05											
			b												

H<sub>2</sub>SO<sub>4</sub> (93 - 98%): Properties Molar Mass: 98.07g/mol

Density: 1.84 g/ml Molarity: 18 moles/litre Normality: 36 moles/litre Release Date:

October 24, 2014

**Expiry Date:** 

October 24, 2017







# **Product Integrity:**

Based on extensive testing results, SEASTAR CHEMICALS INC have found our products, unopened and sealed, maintain the certified integrity, or product quality, for a minimum of three years under the following conditions:

- Stored at room temperature, maximum range 15°C (59°F) to 25°C (77°F).
- Minimum exposure to light.
- For limited time, storage/transport temperature range 5°C (41°F) to 35°C (95°F)

Upon opening the product, the product's integrity will depend on proper handling and exposure to contaminants. The product has been bottled under CLASS 100 clean room conditions, to maintain the certified quality it should be used under these conditions. Furthermore to reduce trace metal contamination, the inner pack of plastic bags and bottle should be opened under CLASS 100 particle conditions to maintain the integrity of the product. The use of plastic gloves, hair net and a clean room suit is also advised.

### Safety:

PRIOR to opening or storing this product be sure to consult the Material Safety Data Sheet (MSDS) Section 7 Handling and Storage to ensure safe storage and handling with regards to this hazardous material. This information must be understood prior to its use or storage.

SAFETY HANDLING NOTES: Consult your MSDS, PRIOR to handling these materials. Use proper safety apparel according to the recommendations of the MSDS. Exposure controls and personal protection should include: a properly functioning fume hood, protection for eyes (safety glasses), hands (chemically compatible gloves), feet (chemically compatible boots) and exposed skin (splash protection and a chemically compatible apron). All of these items must conform to local/regional/national regulatory requirements.

Dr. B. McKelvey QA/QC Manager

B MªZ

10005 McDonald Park Road, Sidney, BC, Canada V8L 5Y2

phone: (250) 655-5880 fax: (250) 655-5888

toll free: 1 (800) 663-2330 (within Canada & U.S. only) Email: <a href="mailto:seastar.technicals.upport@seastarchemicals.com">seastar.technicals.upport@seastarchemicals.com</a>

Web: www.seastarchemicals.com