CERTIFICATE OF ANALYSIS

BASELINE® Hydrofluoric Acid

| 1A | PRODUCT NUMBER: \$020502 (BA-05) LOT NUMBER: 5208040 | | | | | | | | | | ASSAY (HF, w/w): 48% | | | | | | |
|--------------------|------------------------------------------------------|------------------------------------|------------------------------------------|--------------------------|--------------------------------------------------------------------------|---------------------------------------------|-----------------------------------------------|------------------------------------------------|-----------------------------------------|------------------------------------------------------------|--------------------------------------|--------------------|-------------------|-------------------|-------------------|----|--|
| 3 Li < 1 | 2A 4 Be < 5 | average evaporate Nitric Aci | of three alied to drynes d. Operation | quots subsass, the resul | by magnetic ampled fron ting residue ducted und acid samples | n three sam is reconstitu er Class 10 | nples repres uted in a sm 00 particle o | sentative of all volume or or better cle | the lot. The f2% SEAS ean-room co | e samples a FAR [™] BAS enditions. F | are slowly SELINE® or volatile | 3A 5 B < 10 | 4A | 5A | 6A | 7A | |
| 11 Na < 10 | < 5 | times the 3B | standard do | eviation of th 5B | ne blank are 6B | shown with 7B | "<", no blan | k value is su 8 | btracted. | 1B | 2B | < 10 | | | | | |
| 19 K < 10 | 20 Ca < 10 | 21 Sc < 1 | 22 Ti < 10 | 23 V < 1 | 24 Cr < 10 | 25 Mn < 1 | 26 Fe < 10 | 27 Co < 1 | 28 Ni < 10 | 29 Cu < 10 | 30 Z n < 5 | 31 Ga < 1 | 32 Ge < 1 | 33 As < 10 | 34 Se < 50 | | |
| 37 Rb < 1 | 38 Sr < 1 | 39 Y < 0.5 | 40 Zr < 10 | 41 Nb < 5 | 42 Mo < 5 | | 44 Ru < 1 | 45 Rh < 1 | 46 Pd < 10 | 47 Ag < 1 | 48 Cd < 0.1 | 49 In < 0.1 | 50 Sn < 10 | 51 Sb < 10 | 52 Te < 1 | | |
| 55 Cs < 0.5 | 56 Ba < 5 | 57 La < 0.1 | 72 Hf < 1 | 73 Ta < 20 | 74 W < 10 | 75 Re < 0.1 | | | 78 Pt < 10 | 79 Au < 10 | 80 Hg < 20 | 81 TI < 0.1 | 82 Pb < 1 | 83 Bi < 0.1 | | | |

ALL VALUES ARE REPORTED IN PARTS PER TRILLION (PPT)

KEY (1) (2) (3) (4)

(1) Atomic Number

(2) Elemental Symbol

(3) Concentration (mean in ppt)

(4) 1 Standard Deviation (N=3)

| 58 Ce | 59 Pr | 60 Nd | 62 Sm | 63 Eu | 64 Gd | 65 Tb | 66 Dy | 67 Ho | 68 Er | 69 Tm | 70 Yb | 71 Lu |
|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| < 0.1 | < 0.1 | < 0.1 | < 0.1 | < 0.1 | < 0.1 | < 0.1 | < 0.1 | < 0.1 | < 0.1 | < 0.1 | < 0.1 | < 0.1 |
| | | | | | | | | | | | | |
| 90 Th | | 92 U | | | | | | | | | | |
| < 0.1 | | < 0.1 | | | | | | | | | | |
| 10.1 | | 0.1 | | | | | | | | | | |



HF (47 - 51%): Properties

Molar Mass: 20.01g/mol
Density: 1.18 g/ml
Molarity: 29 moles/litre

Normality: 29 moles/litre

Analyte Maximum Actual
Specification Value (in ppb)

Total Sulphur (S) 100 ppb < 50

Release Date: Expiry Date:

June 26, 2008 June 26, 2011

3 Mer

Dr. B. McKelvey QA/QC Manager



Product Integrity:

Based on extensive testing results, SEASTAR CHEMICALS INC have found our products, unopened and sealed, maintain the certified integrity, or product quality, for a minimum of three years under the following conditions:

- Stored at room temperature, maximum range 15°C (59°F) to 25°C (77°F).
- Minimum exposure to light.
- For limited time, storage/transport temperature range 5°C (41°F) to 35°C (95°F)

Upon opening the product, the product's integrity will depend on proper handling and exposure to contaminants. The product has been bottled under CLASS 100 clean room conditions, to maintain the certified quality it should be used under these conditions. Furthermore to reduce trace metal contamination, the inner pack of plastic bags and bottle should be opened under CLASS 100 particle conditions to maintain the integrity of the product. The use of plastic gloves, hair net and a clean room suit is also advised.

Safety:

PRIOR to opening or storing this product be sure to consult the Material Safety Data Sheet (MSDS) Section 7 Handling and Storage to ensure safe storage and handling with regards to this hazardous material. This information must be understood prior to its use or storage.

SAFETY HANDLING NOTES: Consult your MSDS, PRIOR to handling these materials. Use proper safety apparel according to the recommendations of the MSDS. Exposure controls and personal protection should include: a properly functioning fume hood, protection for eyes (safety glasses), hands (chemically compatible gloves), feet (chemically compatible boots) and exposed skin (splash protection and a chemically compatible apron). All of these items must conform to local/regional/national regulatory requirements.

Dr. B. McKelvey QA/QC Manager

B Mª Z

10005 McDonald Park Road, Sidney, BC, Canada V8L 5Y2

phone: (250) 655-5880 fax: (250) 655-5888

toll free: 1 (800) 663-2330 (within Canada & U.S. only) Email: seastar.technicals.upport@seastarchemicals.com

Web: www.seastarchemicals.com