CERTIFICATE OF ANALYSIS

BASELINE® Ammonia Solution

1A	PRODUCT NU	JMBER: S0207	01 LOT	NUMBER: 7214	1100 AS	SAY (NH ₃ ,	w/w): 21%	0	
2A 3 Li 4 B < 0.01 < 0.00 11 Na 12 N < 10 < 0.5	average of three all evaporated to dryne Nitric Acid / 2% Hyd For volatile element	liquots subsampled from less. The resulting reside rogen Peroxide. Operate its (indicated by *), the ac	m three samples repro ue is reconstituted in a ions are conducted un cid samples are diluted	g sample preconcentration resentative of the lot. The small volume of SEAST, ander Class 100 or better of then directly injected in c', no blank value is subtra	e samples are slowly AR™ BASELINE® 2% lean-room conditions. to the ICP-MS. Values	3A	4A 5A	6A 7A	
10 10.0	3B 4B	5B 6B	7B	8	1B 2B				
19 K 20 C	a 21 Sc 22 Ti < 0.1 < 0.1	23 V 24 Cr < 0.5 < 0.05			29 Cu 30 Zn < 0.1 < 0.5	31 Ga 32 < 0.01 <	Ge 33 As 0.01 < 1	34 Se	
37 Rb 38 S < 0.01 < 0.08		41 Nb 42 Mc < 0.05	44 R	Ru 45 Rh 46 Pd < 0.01 < 1	47 Ag 48 Cd < 0.01	49 In 50 < 0.01 <	Sn 51 Sb 0.05 < 0.01	52 Te < 0.05	
55 Cs 56 E < 0.01 < 0.08		73 Ta 74 W < 0.05	75 Re < 1	78 Pt < 1	79 Au 80 Hg < 1 < 100	81 TI 82 < 0.01	Pb 83 Bi 0.05 < 0.01		

ALL VALUES ARE REPORTED IN PARTS PER TRILLION (PPT)

ı	NE I	.(1)	Alonnic
ı	(1) (2)	(2)	Elemen
ı	(3)	(3)	Concen
ı	(4)		in p

KEY (1) Atomic Number

(2) Elemental Symbol(3) Concentration (mean in ppt)

(4) 1 Standard Deviation (N=3)

58 Ce	59 Pr	60 Nd	62 Sm	63 Eu	64 Gd	65 Tb	66 Dy	67 Ho	68 Er	69 Tm	70 Yb	71 Lu
< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01
- 184												
90 Th		92 U										
< 0.01	L.	< 0.01										
	1											



NH₃ (20 - 22%): Properties
Molar Mass: 17.03g/mol
Density: 0.92 g/ml
Molarity: 11 moles/litre
Normality: 11 moles/litre

3 Mer

Dr. B. McKelvey QA/QC Manager

Release Date: November 5, 2014 Expiry Date: November 5, 2017

Product Integrity:

Based on extensive testing results, SEASTAR CHEMICALS INC have found our products, unopened and sealed, maintain the certified integrity, or product quality, for a minimum of three years under the following conditions:

- Stored at room temperature, maximum range 15°C (59°F) to 25°C (77°F).
- Minimum exposure to light.
- For limited time, storage/transport temperature range 5°C (41°F) to 35°C (95°F)

Upon opening the product, the product's integrity will depend on proper handling and exposure to contaminants. The product has been bottled under CLASS 100 clean room conditions, to maintain the certified quality it should be used under these conditions. Furthermore to reduce trace metal contamination, the inner pack of plastic bags and bottle should be opened under CLASS 100 particle conditions to maintain the integrity of the product. The use of plastic gloves, hair net and a clean room suit is also advised.

Safety:

PRIOR to opening or storing this product be sure to consult the Material Safety Data Sheet (MSDS) Section 7 Handling and Storage to ensure safe storage and handling with regards to this hazardous material. This information must be understood prior to its use or storage.

SAFETY HANDLING NOTES: Consult your MSDS, PRIOR to handling these materials. Use proper safety apparel according to the recommendations of the MSDS. Exposure controls and personal protection should include: a properly functioning fume hood, protection for eyes (safety glasses), hands (chemically compatible gloves), feet (chemically compatible boots) and exposed skin (splash protection and a chemically compatible apron). All of these items must conform to local/regional/national regulatory requirements.

Dr. B. McKelvey QA/QC Manager

B MªZ

10005 McDonald Park Road, Sidney, BC, Canada V8L 5Y2

phone: (250) 655-5880 fax: (250) 655-5888

toll free: 1 (800) 663-2330 (within Canada & U.S. only) Email: seastar.technicals.upport@seastarchemicals.com

Web: www.seastarchemicals.com