CERTIFICATE OF ANALYSIS BASELINE[®] Ammonia Solution

		PRODUCT NUMBER: S020701					LOT NUMBER: 7217030					ASSAY (NH ₃ , w/w): 20%					
3 Li < 0.05	2A 4 Be < 0.02	average evaporat	of three ali ed to dryne	quots subs ss. The resi	ampled from ulting residu	n three san e is reconst	nples repres	sentative of mall volume	concentratio the lot. The of SEASTA 0 or better cl	e samples a ∖R [™] BASEL	are slowly _INE [®] 2%	3A	4A	5A	6A	7A	
11 Na < 5	12 Mg < 1	For volat	ile elements	s (indicated	by *), the ac	id samples	are diluted	then directly	injected intended intended intended in the second sec	o the ICP-N		13 AI < 5					
19 К <1	20 C a < 10	21 Sc < 0.01	22 Ti < 0.5	23 V < 2	24 Cr < 0.1	25 Mn < 0.02		27 Co < 0.01	28 Ni < 10	29 C u < 0.5	30 Zn < 2	31 Ga < 0.01	32 Ge < 1	33 As < 0.5	34 Se < 5		
37 Rb < 0.01	38 Sr < 0.02	39 Y < 0.01	40 Zr < 0.01	41 Nb < 0.01	42 Mo < 0.05		44 Ru < 0.01	45 Rh < 0.01	46 Pd < 0.1	47 Ag < 0.05		49 In < 0.01	<mark>50 Sn</mark> < 0.1	51 Sb < 0.01	52 Te < 0.05		
55 Cs < 0.01	56 Ba < 0.05	57 La < 0.01	72 Hf < 0.1	73 Ta	74 W < 1	75 Re < 0.01			78 Pt < 0.1	79 Au < 0.5	80 Hg < 200	81 TI < 0.01	82 Pb < 1	83 Bi < 0.01			
		1.00							-		e						

ALL VALUES ARE REPORTED IN PARTS PER TRILLION (PPT)

(1) (2) (2) Elemental Symbol (3) (3) Concentration (mean	58 Ce < 0.01	59 Pr < 0.01	60 Nd < 0.01	62 Sm < 0.01	63 Eu < 0.01	64 Gd < 0.01	65 Tb < 0.01	66 Dy < 0.01	67 Ho < 0.01	68 Er < 0.01	69 Tm < 0.01	 71 Lu < 0.01
(4) in ppt)	90 Th < 0.01		92 U < 0.01		1					•		

QA & RA Manager

<u>NH₃ (20 - 22%): Properties</u> Molar Mass: 17.03g/mol Density: 0.92 g/ml Molarity: 11 moles/litre Normality: 11 moles/litre



1Δ

Bry Herner Greg Henson Release Date: Expiry Date:

May 02, 2017 May 02, 2020

OT SEAS





Product Integrity:

Based on extensive testing results, SEASTAR CHEMICALS INC have found our products, unopened and sealed, maintain the certified integrity, or product quality, for a minimum of three years under the following conditions:

- Stored at room temperature, maximum range 15°C (59°F) to 25°C (77°F).
- Minimum exposure to light.
- For limited time, storage/transport temperature range 5°C (41°F) to 35°C (95°F)

Upon opening the product, the product's integrity will depend on proper handling and exposure to contaminants. The product has been bottled under CLASS 100 clean room conditions, to maintain the certified quality it should be used under these conditions. Furthermore to reduce trace metal contamination, the inner pack of plastic bags and bottle should be opened under CLASS 100 particle conditions to maintain the integrity of the product. The use of plastic gloves, hair net and a clean room suit is also advised.

Safety:

PRIOR to opening or storing this product be sure to consult the Material Safety Data Sheet (MSDS) Section 7 Handling and Storage to ensure safe storage and handling with regards to this hazardous material. This information must be understood prior to its use or storage.

SAFETY HANDLING NOTES: Consult your MSDS, PRIOR to handling these materials. Use proper safety apparel according to the recommendations of the MSDS. Exposure controls and personal protection should include: a properly functioning fume hood, protection for eyes (safety glasses), hands (chemically compatible gloves), feet (chemically compatible boots) and exposed skin (splash protection and a chemically compatible apron). All of these items must conform to local/regional/national regulatory requirements.

Bregterin

Greg Henson QA & RA Manager

10005 McDonald Park Road, Sidney, BC, Canada V8L 5Y2 phone: (250) 655-5880 fax: (250) 655-5888 toll free: 1 (800) 663-2330 (within Canada & U.S. only) Email: <u>seastar.technicalsupport@seastarchemicals.com</u> Web: <u>www.seastarchemicals.com</u>