BASELINE® Hydrobromic Acid

1A	PRODUCT NUMBER: S020801 LOT NUMBER: 8209100												ASSAY (HBr, w/w): 47%						
3 Li < 1	2A i 4 Be																		
< 20	12 Mg < 5	elements times the 3B	(indicated standard do 4B	by *), the a eviation of th 5B	cid samples ne blank are 6B	are diluted shown with 7B	I then direc "<", no blan	tly injected k value is su 8	into the ICP ubtracted.	-MS. Value 1B	s below 3 2B	13 AI < 50							
19 K < 10	20 Ca < 50	21 Sc < 1	22 Ti < 10	23 V < 1	24 Cr < 10	25 Mn < 2	26 Fe < 50	27 Co	28 Ni < 10	29 C u < 5	30 Zn < 5	31 Ga < 10							
37 Rb	38 Sr < 1	39 Y < 1	40 Zr < 1	41 Nb < 1	42 M o < 20		44 Ru < 10	45 Rh < 1	46 Pd < 10	47 Ag < 2	48 Cd < 1	49 In < 1	50 Sn < 20	51 Sb < 50	52 Te < 10				
55 Cs < 0.05	56 Ba	57 La < 0.05	72 Hf < 0.05	73 Ta < 20	74 W < 10	75 Re < 5			78 Pt < 1	79 Au < 1		81 TI < 0.1	82 Pb < 1	83 Bi < 0.1					

ALL VALUES ARE REPORTED IN PARTS PER TRILLION (PPT)

<u> </u>	_(I) Atomi
(1) (2)	(2) Elem
(3)	(3) Conc
(4)	ir
	^J (4) 1 Sta

ic Number

ental Symbol centration (mean

n ppt) ndard Deviation (N=3)

	58 Ce	59 Pr	60 Nd	62 Sm	63 Eu	64 Gd	65 Tb	66 Dy	67 Ho	68 Er	69 Tm	70 Yb	71 Lu
	< 0.05	< 0.05	< 0.05	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01
۱	- 1												
	90 Th		92 U										
1	< 0.05		< 0.01										


Molar Mass: 80.91g/mol Density: 1.5 g/ml

HBr (44 - 49%): Properties

Molarity: 9 moles/litre Normality: 9 moles/litre **Expiry Date:** November 18, 2012

Release Date:







November 18, 2009

Product Integrity:

Based on extensive testing results, SEASTAR CHEMICALS INC have found our products, unopened and sealed, maintain the certified integrity, or product quality, for a minimum of three years under the following conditions:

- Stored at room temperature, maximum range 15°C (59°F) to 25°C (77°F).
- Minimum exposure to light.
- For limited time, storage/transport temperature range 5°C (41°F) to 35°C (95°F)

Upon opening the product, the product's integrity will depend on proper handling and exposure to contaminants. The product has been bottled under CLASS 100 clean room conditions, to maintain the certified quality it should be used under these conditions. Furthermore to reduce trace metal contamination, the inner pack of plastic bags and bottle should be opened under CLASS 100 particle conditions to maintain the integrity of the product. The use of plastic gloves, hair net and a clean room suit is also advised.

Safety:

PRIOR to opening or storing this product be sure to consult the Material Safety Data Sheet (MSDS) Section 7 Handling and Storage to ensure safe storage and handling with regards to this hazardous material. This information must be understood prior to its use or storage.

SAFETY HANDLING NOTES: Consult your MSDS, PRIOR to handling these materials. Use proper safety apparel according to the recommendations of the MSDS. Exposure controls and personal protection should include: a properly functioning fume hood, protection for eyes (safety glasses), hands (chemically compatible gloves), feet (chemically compatible boots) and exposed skin (splash protection and a chemically compatible apron). All of these items must conform to local/regional/national regulatory requirements.

Dr. B. McKelvey QA/QC Manager

10005 McDonald Park Road, Sidney, BC, Canada V8L 3S8

phone: (250) 655-5880 fax: (250) 655-5888

toll free: 1 (800) 663-2330 (within Canada & U.S. only) Email: seastar.technicals.upport@seastarchemicals.com

Web: www.seastarchemicals.com