BASELINE® Water

2A 3 Li	1A	1 6	PROD	UCT NU	JMBER	: S0209	01						LOT N	JMBER	: 92110	40		
19 K 20 Ca 21 Sc 22 Ti 23 V 24 Cr 25 Mn 26 Fe 27 Co 28 Ni 29 Cu 30 Zn 31 Ga 32 Ge 33 As* 34 Se* < 10 < 10 < 1 < 5 < 1 < 10 < 1 < 10 < 1 < 10 < 5 < 5 < 1 < 1 < 10 < 50 < 5	11 Na	4 Be < 1	average evaporat Nitric Aci For volat 3 times th	of three ali ted to dryne d / 2% Hydr ile elements ne standard	quots subs ss. The resi ogen Perox s (indicated l deviation of	ampled fron ulting residu ide. Operati by *), the sar the blank ar	n three san e is recons ons are cor mples are di re shown wi	nples repre- tituted in a s nducted und iluted then d	sentative of small volume ler Class 10 lirectly injec	the lot. The of SEASTA or better code into the l	e samples AR™ BASE lean-room o CP-MS. Va	are slowly LINE® 2% conditions. lues below	5 B < 20	4A	5A	6A	7A	
				22 Ti	23 V	24 Cr	25 Mn				29 Cu	30 Zn						
											_							
55 Cs 56 Ba 57 La 72 Hf 73 Ta 74 W 75 Re <																		

ALL VALUES ARE REPORTED IN PARTS PER TRILLION (PPT)

KEY (1) (2) (3)

(1) Atomic Number

(2) Elemental Symbol (3) Concentration (mean

in ppt) (4) 1 Standard Deviation (N=3)

ſ	58 Ce	59 Pr	60 Nd	62 Sm	63 Eu	64 Gd	65 Tb	66 Dy	67 Ho	68 Er	69 Tm	70 Yb	71 Lu
	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
								-					
Ī	90 TI		92 U										
1	< 0.1		< 0.1										
					_								

Additional	Maximum	Actual
Tests	Specification	Value
Colour (APHA)	10 APHA	< 10
Chloride (CI-)	1 ppb	< 1
Phosphate (PO ₄ ³ -)	1 ppb	< 1
Sulphate (SO ₄ ²⁻)	1 ppb	< 1

Release Date: **Expiry Date:** May 10, 2011 May 10, 2014



Dr. B. McKelvey QA/QC Manager



Product Integrity:

Based on extensive testing results, SEASTAR CHEMICALS INC have found our products, unopened and sealed, maintain the certified integrity, or product quality, for a minimum of three years under the following conditions:

- Stored at room temperature, maximum range 15°C (59°F) to 25°C (77°F).
- Minimum exposure to light.
- For limited time, storage/transport temperature range 5°C (41°F) to 35°C (95°F)

Upon opening the product, the product's integrity will depend on proper handling and exposure to contaminants. The product has been bottled under CLASS 100 clean room conditions, to maintain the certified quality it should be used under these conditions. Furthermore to reduce trace metal contamination, the inner pack of plastic bags and bottle should be opened under CLASS 100 particle conditions to maintain the integrity of the product. The use of plastic gloves, hair net and a clean room suit is also advised.

Safety:

PRIOR to opening or storing this product be sure to consult the Material Safety Data Sheet (MSDS) Section 7 Handling and Storage to ensure safe storage and handling with regards to this hazardous material. This information must be understood prior to its use or storage.

SAFETY HANDLING NOTES: Consult your MSDS, PRIOR to handling these materials. Use proper safety apparel according to the recommendations of the MSDS. Exposure controls and personal protection should include: a properly functioning fume hood, protection for eyes (safety glasses), hands (chemically compatible gloves), feet (chemically compatible boots) and exposed skin (splash protection and a chemically compatible apron). All of these items must conform to local/regional/national regulatory requirements.

Dr. B. McKelvey QA/QC Manager

B Mª M

10005 McDonald Park Road, Sidney, BC, Canada V8L 5Y2

phone: (250) 655-5880 fax: (250) 655-5888

toll free: 1 (800) 663-2330 (within Canada & U.S. only) Email: seastar.technicals.upport@seastarchemicals.com

Web: www.seastarchemicals.com